

L (mm)	250	500	750	1000	1500	2000	3000
Artikel-Nr.	L00010A1804	L00010A1805	L00010A1806	L00010A1807	L00011A1456	L00011A1457	L00012A1458
L (mm)	5000	10000					
Artikel-Nr.	L00013A1459	L00015A1461					

Mechanical characteristics

connector standard
 cable specifications see
 mating life

Components

centre contact
 outer contact
 crimp ferrule
 other metal parts
 insulator
 gasket
 strain relief

Electrical characteristics

impedance
 voltage proof
 insulation resistance

Environmental

operating temp.
 RoHS compliant

Mechanische Eigenschaften

Steckverbinder-Norm
 Kabelspezifikation siehe
 Steckzyklen

Bauteile

Innenkontakt
 Außenkontakt
 Crimprohr
 sonstige Metallteile
 Isolierung
 Dichtung
 Knickschutzülle

Elektrische Eigenschaften

Wellenwiderstand
 Prüfspannung
 Isolationswiderstand

Umgebung

Betriebstemperatur
 RoHS konform

IEC61169-8
 L01001A0001
 >500

Materials / Material


CuZn39Pb3
 CuZn39Pb3
 Cu SF w
 GD-ZnAl4Cu1
 PE-LD
 silicone / Silikon
 PVC (black / schwarz)

Finish / Oberfläche

NiP-Au
 Cu2Ni5
 Ni5
 Zn/Cu6Ni6

75 Ω
 1,5 kV_{eff} / 50 Hz
 ≥ 5 GΩ

-30°C / +75°C
 2011/65/EU

Änd./ rev. index	Änderungs-Nr. / revision code	Datum/ date	Name/ name	gez./ drawn	Datum/ date	Name/ name	Gewicht/ weight [g]				
					25.03.2020	MA					
				gepr./ appr.	26.03.2020	BJ	ca./approx.				
				Maßstab/ scale	Benennung/ title						
				1:1	RF Cable Assembly HF-Kabel kpl. RG-59B/U						
				Unterl./ doc. type	Zeichnungsnr./ drawing no.						
				K	L00010A1804						
				Ersatz für/ replaces							
											
								Maße/ dimensions: mm			
								Original : DIN A4			
				Blatt/ sheet 1 von/ of 1							