

Mechanical characteristics
interface dimensions acc. to

Mechanische Eigenschaften
Steckgesicht nach

MIL-STD-348A

Components

centre contact
outer contact
other metal parts
insulator

Bauteile

Innenkontakt
Außenkontakt
sonstige Metallteile
Isolierung

Materials / Material

brass / Messing
brass / Messing
brass / Messing
PTFE

Finish / Oberfläche

gold plated / vergoldet
nickel plated/ vernickelt
nickel plated/ vernickelt

Electrical characteristics

impedance
frequency
voltage rating

Elektrische Eigenschaften

Wellenwiderstand
Frequenz
Betriebsspannung

50 Ω
0-2,5 GHz
max. 335 V



Environmental

operating temp.
RoHS compliant

Umgebung

Betriebstemperatur
RoHS konform

-55°C / +85°C
2011/65/EU

Änd./ rev. index	Änderungs-Nr. / revision code	Datum/ date	Name/ name	gez./ drawn	Datum/ date	Name/ name	Gewicht/ weight [g]
				gepr./ appr	22.03.2018	KL	
				Maßstab/ scale	Benennung/ title		
				2:1	Adaptor UHF-Mini UHF (m-f) Adaptor UHF-Mini UHF (m-f)		
				Untert./ doc. type	Zeichnungsnr./ drawing no.		
				K	J01043F0002		
				Ersatz für/ replaces			
							
				 Maße/ dimensions: mm			
				Original : DIN A4			
				Blatt/ sheet 1 von/ of 1			